





POS PRINTER SAT

- Thermal printer
- High printing speed up to 100mm / s
- Low energy consumption, energy efficient and friendly to the environment
- Splash-proof and dust-proof

BENEFITS

- Ergonomic, elegant and compact design.
- Versatile machine, two connection interfaces (USB / SERIAL)
- Friendly with the environment, Energy Star certification.
- Easy loading of paper.
- · Connection for cash drawer.

APPLICATIONS



terminals



Restaurants



Supermarkets



Parking lots







Retailers



Hotels







Bars









Manufacture





Business

PORTS



USB





WARRANTY



We have the necessary personal and infrastructure to give you an excellent Post-Purchase service.

DESCRIPTION

The thermal printer SAT 15T, is a high quality product with an ergonomic design, thought for small spaces that request optimum print quality, its practical design avoids the excesses of dust and water. Easy to clean and remove grease, which makes it an ideal printer for any market.

We have EnergyStar certification to indicates that this product is also friendly to the environment by reducing Co2 footprint.









TECHNICAL ESPECIFICATIONS

ESPECIFICATIONS		DESCRIPTION
Printing	Printing method	Direct thermal
	Resolution	203dpi (8dots/mm)
	Print speed	Max.100mm/s
	Printing width	48mm
Interface	Standard	USB + Serial
Memory	Flash	16Mb
Fonts	Alphanumeric	ASCII 8X16, 12X24 dots
	User-defined	YES
	codepage	48 mm
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE39,
	2D	QR CODE
Graphics		Support bitmap printing and user defined bitmap printing. (Max. 40k per bitmap, and Max. 64k for total)
Sensors		Paper out sensor, cover open switch.
LED Indicator	Power	Green LED
	Error	Red LED
Reliability	Thermal print head (TPH)	100km
Power supply	AC Input	100V-240V
	DC Output	12V/2A
Paper	Paper type	Thermal receipt paper
	Paper width	58mm
	Paper thickness	0.056 ~ 0.1mm
	Paper roller diameter	Máx. Ø 83mm
	paper loading	Easy paper loading
Environment	Operation	0°C ~ 40°C, 20% ~85% RH
	Storage	-20°C ~ 70°C, 5% ~95% RH
Physical Characteristics	Dimension	186mm*L x 114*W x 128*H
	Weight	1.06Kg (Without paper roll)
Accessories		USB/ Serial cable, paper roll, power adapter, Power cord, CD, Quick start guide
Software	Emulation	ESC/POS
	Driver	Windows/posReady/Linux/ OPOS